

2026



İPK MÜHENDİSLİK
VE TEST CİHAZLARI

PRODUCT CATALOG

Automotive Type Approval (Homologation) Test Solutions



www.ipkmuhendislik.com - Your Partner in Engineering Solution



Braking Test Unit

Braking Test Unit

UNECE R13 and EU2015/68 Compliant Braking Test Unit



CAN-Bus Protocol :
Full compliance with ISO 11992 communication protocols

High Sampling Rate: High-speed Data Acquisition (DAQ) at 1 kHz and above for millisecond-accurate response time measurements.

User-Friendly Interface: PC-based test management featuring real-time graphical analysis and automated reporting.



M, N and T Category Vehicles (Motor Vehicles)


Annex 6 - Response Time

"Precision Timing via Dual-Switch Triggering"

The R13-TU features an advanced brake pedal trigger mechanism equipped with dual high-speed switches to eliminate operator-induced latency.

Initial Contact Switch (T0): Captures the exact millisecond the pedal begins its travel, fulfilling the ECE R13 requirement for starting the response time clock.

Full-Stroke Switch (Tmax): Identifies the moment of maximum displacement, allowing for a comprehensive analysis of the system's pressure build-up curve.



Trailers

Annex 6: Response Time Testing The system simulates the towing vehicle by delivering instantaneous pneumatic pressure or digital signals (braking via CAN-Bus) to the control line. It captures and records data from trailer-mounted pressure sensors with millisecond precision.

Automatic Reservoir Capacity Validation (8-Stroke Test) according to ECE R13 Annex 7 This test verifies the capacity of the trailer's air reservoirs to ensure safe braking performance even after the energy source (towing vehicle) is disconnected.





Steering Test Unit

ECE R79 Compliant Steering Test System



Annex 3 Steering Effort Measurement:

Measuring the maximum force (in Newtons) and torque applied by the driver to rotate the steering wheel.

Universal Quick-Mount: Adjustable clamp system for all steering wheel diameters (Trucks, Buses, Cars).

Integrated High-Resolution Torque Sensor: Features a high-precision Kistler Torque Sensor (Accuracy: ± 0.1 Nm).

Steering Test Unit



PC-Independent Operation & Seamless Data Management

Standalone Testing: High-performance integrated controller, the STU can manage the entire testing process without requiring an external PC connection.

Integrated Control Interface: Start tests and monitor real-time data directly through the on-device graphical display.

USB Data Export: Upon test completion, export all high-resolution graph data and measurement results in CSV format directly to a USB flash drive.


Plug-and-Play Analytics: Simply plug the USB drive into your workstation to perform advanced data analysis using standard spreadsheet software (Excel, etc.).





Steering Lock Test Unit


BM ECE R18 Compliant Steering Lock and Unauthorized Use Test System



Durability Test

Independent Operation and Intelligent Control:

HMI-Based Testing: Perform complex durability and strength tests directly via the high-resolution touchscreen. No external computer is required.



Dual Servo Precision: Equipped with two high-performance servo motors for independent torque control of the ignition switch and steering column.

Steering Lock Test Unit

Innovative "Manual Teaching" Mode

Steering Wheel Position Learning:

Easily identify the left and right locked positions by manually rotating the steering wheel; the system records these coordinates with a single click.




Mechanical Flexibility and Ergonomics

Symmetric Modular Design:

The entire system is built on a mirrored architecture. The ignition servo and mounting hardware can be easily switched from left to right, allowing testing for both left-hand drive (LHD) and right-hand drive (RHD) vehicle configurations.

Multi-Axis Adjustability:

Key Angle and Height: Precise adjustment for various ignition switch geometries.






Chassis Dyno for Motor Cycle

Chassis Dyno for Motor Cycle

Chassis Dynamometer for L-Category Vehicles



EU 134/2014
UNECE R85

Compliant Energy & Performance Validation

Regulation-Ready Road Simulations

WMTC Integration: Fully supports World Motorcycle Test Cycle (WMTC) road simulations as per EU 134/2014.

- Embedded Class Profiles
- Customizable Test Paths

Energy & Range Validation

High-precision measurement systems for energy consumption and electric vehicle range testing.

- Superior Engineering & Hardware
- Industrial Control Power
Driven by the Beckhoff Industrial PC, ensuring real-time control and high-speed data processing.
- Precision Torque and Speed Measurement
Integrated Kistler Torque Sensors
- Specially Balanced Rollers
- Flexible Configuration
Modular design supporting both Single and Dual Roller usage for various vehicle wheelbases.
- Speed-Matched Wind Simulation
Integrated cooling fan system that generates headwind proportional to the actual vehicle speed, ensuring realistic thermal conditions.

Real-Time DataStreaming:

A dynamic, high-resolution speed-time graph flows across the operator dashboard for instantaneous performance monitoring.

Autonomous & Driverless Test Capability



High-Performance Electric Motor Test Bench

ECE R85

- Net Power Measurement
- Maximum 30 Minutes Power Test


Fully compliant with mandatory test procedures, including the 5-minute peak power scan and the 30 minute maximum continuous power test.

Dynamic Performance Mapping:

Real-time generation of torque-speed and power-speed curves as required for electric motor characterization.

Integrated Thermal Management:

System includes an integrated chiller unit for the water-cooled Eddy Current Brake to ensure stabilized results during long-duration (30 min) tests.




High-Speed Eddy Current Brake: Precision water-cooled loading system capable of handling motors up to 16 kW and speeds up to 8,000 RPM

Industrial-grade torque sensing technology ensures laboratory-level accuracy in all power calculations.

Autonomous Cycle Execution: Pre-programmed R85 test sequences allow for fully autonomous execution, minimizing human error and ensuring 100% repeatability.

Real-Time Data Analytics:

Proprietary C# application provides instantaneous visualization of critical parameters: RPM, Torque, Power, and Cooling Temperature.





Conditioned Room & Cabinet

Conditioned Room & Cabinet

Conditioned Rooms & Cabinets



Precision Environmental Control for Regulatory Compliance

- UN ECE R100 - Battery Thermal Conditioning
- UN ECE R118 - Flammability Pre-Conditioning
- WLTP / EU 2017/1151 - Dyno Room Stability
- UN ECE R43 - Safety Glass Testing
- UN ECE R134 - Hydrogen-Powered Vehicles (H2)
- ISO 16750-4 - Climatic Loads for Electronics

High-Precision Stability:

Temperature control accuracy of ± 0.1 °C and humidity control of $\pm 2\%$ RH to meet the strictest homologation standards.

Long-Term Logging & Traceability:

Integrated data acquisition systems that provide 24/7 logging of environmental conditions, essential for technical service audits.

Safety Features for Battery Testing:

Optional fire suppression, gas detection, and pressure relief systems for battery "soak" rooms to ensure lab safety during EV testing.


Programmable Cycles:

User-friendly HMI allows for complex temperature/humidity profiles and automated 24-hour soaking timers.



Dynamic Coupling Component Test System

**UN ECE R55 Compliant
Dynamic Fatigue &
Strength Testing**



UN ECE R55 Mechanical Coupling Validation:

Specifically designed to perform the mandatory dynamic fatigue tests for coupling balls, towing brackets, and drawbeams.


- **Multi-Axis Force Application:**

Capability to apply high-capacity forces

- **High-Frequency Performance:**

Achieves 3-5 Hz for standard dynamic tests, with the ability to reach 5-10 Hz at lower force levels for accelerated fatigue analysis.

- For specialized applications requiring higher frequencies, we offer custom design capabilities up to 35 Hz.



Integrated Test Environment

Soundproof & Conditioned Environment:
The system can be integrated into a specialized sound-insulated and thermally conditioned room to maintain lab safety and result stability.



- **Servo-Proportional Hydraulic Precision:**


High-response servo-proportional valves ensure millisecond-level reaction times and precise force control.

- **Industrial PC-Based Architecture:**

Driven by a powerful industrial PC for high-speed data acquisition and real-time closed-loop control.

- **Fully Customizable Design:**

Force, speed, and mechanical stroke parameters can be tailored; the modular structural design allows for project-specific modifications.






Towing Hitch Testing Unit

Towing Hitch Testing Unit

Dynamic Strength Validation for Towing Devices



Regulation Compliance

- EU 1005/2010 Fully Compliant
- UN ECE R55 Equivalent Technical Standards
- Verified Integrity for Vehicle Towing Devices

- **Rigid Testing Frame:** High-strength steel frame structure compatible with different vehicle classes (M1, N1, etc.).
- **Multi-Vector Force Application:** Advanced actuator system allowing simultaneous or independent application of tensile and vertical loads.

Precision Load Management: Using a closed-loop control system method, it applies forces to the target forces while remaining within the 5% tolerance specified in the regulation.

Integrated Data Analysis:

- **Real-Time Displacement Tracking:** Instantaneous tracking and graphical representation of deformations occurring during testing.
- **Automated Test Cycles:** Automatic control of the staged loading and holding processes required by the regulation.





Heavy-Duty Protective Structure Test System

EU 1322/2014 Compliant Force and Energy Absorption Validation

Specifically engineered to perform mandatory static loading tests for agricultural and forestry vehicle cabins, ensuring the "Clearance Zone" remains protected during a rollover.

Full Control and Traceability via C# Based Visual Studio Suite

Real-Time Synchronized Graphing


Automated Parameter Management

Multi-Axis Manual & Auto Control

One-Click Professional Reporting

Data Export : Excel (.xlsx) and Image (.jpg/png)

Intelligent Software Interface & Data Analytics



Regulatory Force & Energy Testing

- **Lateral Loading (Energy Absorption):** Application of lateral force to simulate side rollovers, calculating the exact energy (kJ) absorbed by the structure to meet regulatory safety thresholds.
- **Longitudinal Loading (Front & Rear):** Testing the structural integrity against longitudinal impacts to verify that the protective frame can withstand forces from front or rear-end collisions.
- **Vertical Crushing Test:** High-capacity vertical load application to simulate the weight of the overturned vehicle, ensuring the structure does not collapse into the operator's space.



Seat Belts Anchorages Test Unit


Seat Belts Anchorages Test Unit

Advanced Seat & Seat Belt Tension Test System




Multi-Regulation Compliance for ECE R14, R16, R21, R80, FMVSS 210 Standards

- **FMVSS 210 - Seat Belt Assembly Anchorages (USA):**
Establishes stringent requirements for seat belt anchorages to ensure their proper location for effective occupant restraint and structural integrity during high-load crash simulations.
- **ECE R14 - Seat Belt Anchorages (EU):**
Specifically designed to perform static strength tests on belt anchorages, ensuring the vehicle structure can withstand extreme loads.
- **ECE R16 - Seat Belt Assembly:**
Validation of the complete seat belt system, including webbing, buckles, and retractors under high-tension requirements.
- **ECE R80 - Strength of Seats (M2 & M3):**
Testing the strength of seats and their anchorages for large passenger vehicles to ensure passenger protection during impacts.
- **ECE R21 - Interior Fittings:**
Verification of interior components to ensure they do not detach or cause injury during high-force scenarios.



- **9-Channel 3x3 Matrix Actuator System:** Features 9 independently controllable servo-actuators in a matrix layout for complex, multi-point synchronized pulling scenarios.
- **Synchronized Load Profiles:** Capability to define individual pull rates and force targets for each actuator, ensuring a perfectly distributed load according to regulation geometry.
- **Industrial PC-Based Architecture:** Driven by a powerful industrial PC for high-speed data acquisition and real-time closed-loop control.
- **C# Visual Studio Based GUI:** Custom-developed software (seen on dashboard) providing real-time monitoring of force-displacement curves for all 9 channels.
- **Professional One-Click Reporting:** Instant generation of detailed Excel and PDF reports including peak force data and graphical analysis for homologation audits.






Short Circuit Test Unit



Short Circuit Test Unit

High-Speed Short Circuit Test Device

UN ECE R100
Compliant Battery
Safety & Short Circuit
Validation



- **UN ECE R100 Battery Behavior Monitoring:** Specifically engineered to observe and analyze the thermal and electrical behavior of electric vehicle batteries during a controlled short-circuit event.
- **Low-Impedance DC Shunt Resistance:** Features a high-precision DC shunt with a resistance of $< 5m\Omega$, ensuring full compliance with strict regulatory requirements for high-current discharge testing.



Ultra-High Speed Data Acquisition

Equipped with specialized high-speed analog input cards, allowing for laboratory-grade precision in extreme conditions.

- **10 Microsecond Sampling Rate:** Captures critical voltage and current data points every $10\mu s$ (100kHz), providing a high-resolution map of the battery's reaction in the first microseconds of the short circuit.
- **Real-Time Synchronized Control:** Powered by the industrial PC architecture to ensure ultra-low latency and perfect synchronization between current measurement and safety interlocks.
- **USB Data Export:** Upon test completion, export all high-resolution graph data and measurement results in CSV format directly to a USB flash drive.



• Plug-and-Play Analytics:

Simply plug the USB drive into your workstation to perform advanced data analysis using standard spreadsheet software (Excel, etc.).



TPMS Simulator

TPMS Simulator

UN ECE R141 Compliant TPMS Simulator

ECE R141 Protocol Accuracy: Fully compliant with ECE R141 CAN-Bus protocols and message intervals, ensuring seamless communication with all EU-standard vehicles.

Industrial Reliability: Built into a high-durability transit case for field testing and lab environments, featuring robust industrial PCB design.





Towing Vehicle Simulation Mode:


Acts as the towing vehicle to capture and decode TPMS messages originating from the trailer. It visualizes pressure and temperature for up to 6 tires while monitoring all TPMS-related network traffic.

Detailed Data Logging:

Capable of capturing and recording all incoming CAN messages in Excel (.xlsx) format for comprehensive auditing and reporting.




Advanced CAN-Bus Simulation for Tyre Pressure Monitoring Systems



Trailer Simulation Mode :

Acts as a smart trailer to simulate TPMS CAN messages sent to the towing vehicle. It allows the user to configure axle/wheel layouts and transmit real-time pressure and temperature data.

Supports mandatory status messaging: Sufficient, Insufficient, Error Indicator, and Not Available. Used to verify dashboard warning lights and the accuracy of the vehicle's onboard computer.






Tractor Test Unit

Tractor Test Unit

EU 2015/68 Compliant Tractor Braking Test System



- **EU 2015/68 Dual-Line Hydraulic Compliance:** Specifically engineered for tractors equipped with dual hydraulic line braking systems to ensure full compliance with European safety standards.
- **Precision Response Time Analysis:** Accurately measures the time interval from the moment the brake pedal is actuated until the target pressure is reached, fulfilling strict regulatory timing requirements.
- **Handbrake & Breakaway Verification:** Automated testing of the parking brake effectiveness and the emergency breakaway function to ensure the trailer remains safe even in decoupling scenarios.

Ana Sayfa

TTU test cihazının mekanik bağlantılarını tamamlayın ve basınç sensörü kablolarını TTU Kontrolcüsüne bağlayın.

Teste başlamak için TTU Kontrolcüsü haberleşme kablosunu bilgisayarınıza takın, port seçimi yapın ve bağlan butonuna tıklayın

Kalibrasyon sayfası için basınç sensörü kablolarını TTU Kontrolcüsüne bağlayın ve TTU Kontrolcüsü haberleşme kablosunu bilgisayarınıza takın, port seçimi yapın ve bağlan butonuna tıklayın

Organizasyon

Üretici

Araç Tipi

Testi Yapan

Test Rapor Numarası

Şasi Numarası

Basınç Sensörü Kalibrasyon Tarihi

1 Ocak 2019 Salı

TTU Kontrolör

Yenile

Bağlan

Bağlantıyı Kes

Bağlantı Durumu: Bağlanmadı

Tepki Süresi Testi


Kopma Testi

El Freni Testi

Servis Freni Testi

Kalibrasyon Sayfası

Real-Time Graphical Interface: Feature-rich software dashboard providing live pressure-time curves, allowing operators to monitor the buildup and release phases of the test cycle.



- **Integrated Pressure Simulators:** Equipped with specialized hydraulic reservoirs and simulators to replicate real-world trailer braking loads with high fidelity, supporting operations up to the regulatory maximum of 160 bar.
- **Industrial High-Speed Data Acquisition:** Powered by a robust control unit for millisecond-accurate pressure monitoring and synchronized real-time control.
- **Professional Multi-Format Reporting:** Instant generation of detailed test reports in both PDF and Excel (.xlsx) formats for official certification and internal R&D traceability.




Agricultural Trailer Test Unit


Agricultural Trailer Test Unit

Advanced Agricultural Trailer Test Unit

EU 2015/68 Compliant Testing for Agricultural Trailers (Category R & S)



EU 2015/68 Dual-Line Hydraulic Simulation: Designed to act as a tractor to test agricultural trailers (Category R) and interchangeable towed equipment (Category S) equipped with dual-line hydraulic braking systems.




High-Performance Hydraulic Power Unit: Mobile and robust hydraulic unit capable of providing the necessary pressure and flow rates required for heavy-duty trailer testing.

Integrated Control & Measurement Case: Portable industrial control case featuring high-precision pressure transducers and high-speed data acquisition hardware for on-site testing.



Annex III Response Time Testing: Precisely measures the response time of the trailer's braking system, ensuring the time elapsed between the tractor's command and the trailer's brake activation meets safety limits.






FOPS Test Unit

Precision FOPS Impact & Release System

EU 1322/2014 FOPS Requirements: Specifically designed to perform mandatory drop tests for agricultural and forestry vehicles to verify the cabin's resistance against falling objects.



High-Performance Pneumatic Triggering

Instantaneous Frictionless Release:

The specialized pneumatic trigger body ensures an instantaneous release of the test weight, eliminating mechanical friction and ensuring 100% gravitational accuracy.

Remote Safety Activation:

Pneumatic control allows operators to trigger the release from a safe distance, fulfilling laboratory occupational health and safety (OHS) protocols


Heavy-Duty Modular Design:

The trigger mechanism is constructed from high-strength treated steel (as shown in the technical CAD) to handle repetitive high-mass drop cycles without deformation.



Fuel Consumption Measurement Test Unit

Electric Vehicle Energy Efficiency & Power Analysis System




e-SORT Standardised On-Road Test Cycles: Specifically designed to calculate the energy consumption of electric vehicles according to UITP e-SORT protocols under various operating conditions.

Total Energy & Average Power Calculation: Measures and records total energy consumption (Wh) and average power demand during standardized driving cycles to determine the vehicle's kWh/km efficiency.

High-Precision Power Mapping: Real-time monitoring of voltage and current to map the power delivery characteristics of the battery and drivetrain during acceleration, cruise, and regeneration phases.


Real-Time Dashboard: Features an intuitive interface (as seen in image_37b8d6.png) for monitoring critical parameters: Voltage (V), Current (A), Instantaneous Power (W), and Cumulative Energy (Wh).



On-Board Energy Monitoring Infrastructure



İPK MÜHENDİSLİK
VE TEST CİHAZLARI



İpk Mühendislik ve Test Cihazları San. Tic. Ltd. Şti.

Ramazanoğlu Mh. Sanayi Cd. Kurtköy San. Sit. No:44B/86 Pendik/İstanbul

E-mail: proje@ipkmuhendislik.com