

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
70	73.0	50	42.8		3,254
75	78.0	50	42.8		3,956
75	78.0	55	47.8		3,535
80	83.0	50	42.8		4,705
80	83.0	55	47.8		4,284
80	83.0	60	52.8		3,816
85	88.0	50	42.8		5,501
85	88.0	55	47.8		5,079
85	88.0	60	52.8		4,611
85	88.0	65	57.8		4,097
90	93.0	55	47.8		5,921
90	93.0	60	52.8		5,453
90	93.0	65	57.8		4,939
90	93.0	70	62.8		4,378
95	98.0	55	47.8		6,810
95	98.0	60	52.8		6,342
95	98.0	65	57.8		5,827
95	98.0	70	62.8		5,266
95	98.0	75	67.8		4,659
100	103.0	60	52.8		7,277
100	103.0	65	57.8		6,762
100	103.0	70	62.8		6,201
100	103.0	75	67.8		5,594
100	103.0	80	72.8		4,940
105	108.0	60	52.8		8,258
105	108.0	65	57.8		7,744
105	108.0	70	62.8		7,183
105	108.0	75	67.8		6,575
105	108.0	80	72.8		5,921
105	108.0	85	77.8		5,221
110	113.0	60	52.8		9,286
110	113.0	65	57.8		8,772
110	113.0	70	62.8		8,211
110	113.0	75	67.8		7,603
110	113.0	80	72.8		6,949
110	113.0	85	77.8		6,249
110	113.0	90	82.8		5,502
115	118.0	70	62.8		9,285
115	118.0	75	67.8		8,678
115	118.0	80	72.8		8,024
115	118.0	85	77.8		7,323
115	118.0	90	82.8		6,576
115	118.0	95	87.8		5,783
120	123.0	70	62.8		10,406
120	123.0	75	67.8		9,799

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
120	123.0	80	72.8		9,145
120	123.0	85	77.8		8,444
120	123.0	90	82.8		7,697
120	123.0	95	87.8		6,904
120	123.0	100	92.8		6,063
125	128.0	70	62.8		11,574
125	128.0	75	67.8		10,966
125	128.0	80	72.8		10,312
125	128.0	85	77.8		9,612
125	128.0	90	82.8		8,865
125	128.0	95	87.8		8,071
125	128.0	100	92.8		7,231
125	128.0	105	97.8		6,344
130	134.2	70	62.8		13,086
130	134.2	75	67.8		12,479
130	134.2	80	72.8		11,825
130	134.2	85	77.8		11,124
130	134.2	90	82.8		10,377
130	134.2	95	87.8		9,583
130	134.2	100	92.8		8,743
130	134.2	105	97.8		7,857
130	134.2	110	102.8		6,924
140	144.2	70	62.8		15,676
140	144.2	75	67.8		15,068
140	144.2	80	72.8		14,414
140	144.2	85	77.8		13,714
140	144.2	90	82.8		12,967
140	144.2	95	87.8		12,173
140	144.2	100	92.8		11,333
140	144.2	105	97.8		10,447
140	144.2	110	102.8		9,514
140	144.2	115	107.8		8,534
140	144.2	120	112.8		7,508
150	154.2	40	32.8	10,351	
150	154.2	50	42.8	10,006	
150	154.2	60	52.8	9,571	
150	154.2	70	62.8		18,452
150	154.2	75	67.8		17,845
150	154.2	80	72.8		17,191
150	154.2	85	77.8		16,490
150	154.2	90	82.8		15,743
150	154.2	95	87.8		14,949
150	154.2	100	92.8		14,109
150	154.2	105	97.8		13,223
150	154.2	110	102.8		12,290

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
150	154.2	115	107.8		11,310
150	154.2	120	112.8		10,284
150	154.2	125	117.8		9,211
150	154.2	130	122.8		8,092
160	164.2	40	32.8	11,803	
160	164.2	50	42.8	11,458	
160	164.2	60	52.8	11,022	
160	164.2	70	62.8	10,495	
160	164.2	75	67.8		20,807
160	164.2	80	72.8		20,153
160	164.2	85	77.8		19,452
160	164.2	90	82.8		18,705
160	164.2	95	87.8		17,912
160	164.2	100	92.8		17,071
160	164.2	105	97.8		16,185
160	164.2	110	102.8		15,252
160	164.2	115	107.8		14,272
160	164.2	120	112.8		13,246
160	164.2	125	117.8		12,173
160	164.2	130	122.8		11,054
160	164.2	135	127.8		9,889
160	164.2	140	132.8		8,676
170	174.2	40	32.8	13,346	
170	174.2	50	42.8	13,001	
170	174.2	60	52.8	12,565	
170	174.2	70	62.8	12,038	
170	174.2	80	72.8	11,420	23,301
170	174.2	85	77.8		22,600
170	174.2	90	82.8		21,853
170	174.2	95	87.8		21,060
170	174.2	100	92.8		20,220
170	174.2	105	97.8		19,333
170	174.2	110	102.8		18,400
170	174.2	115	107.8		17,420
170	174.2	120	112.8		16,394
170	174.2	125	117.8		15,322
170	174.2	130	122.8		14,202
170	174.2	135	127.8		13,037
170	174.2	140	132.8		11,825
170	174.2	145	137.8		10,566
170	174.2	150	142.8		9,261
180	184.2	40	32.8	14,980	
180	184.2	50	42.8	14,635	
180	184.2	60	52.8	14,199	
180	184.2	70	62.8	13,672	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
180	184.2	80	72.8		26,635
180	184.2	85	77.8		25,934
180	184.2	90	82.8		25,187
180	184.2	95	87.8		24,394
180	184.2	100	92.8		23,554
180	184.2	105	97.8		22,667
180	184.2	110	102.8		21,734
180	184.2	115	107.8		20,755
180	184.2	120	112.8		19,728
180	184.2	125	117.8		18,656
180	184.2	130	122.8		17,537
180	184.2	135	127.8		16,371
180	184.2	140	132.8		15,159
180	184.2	145	137.8		13,900
180	184.2	150	142.8		12,595
180	184.2	155	147.8		11,243
180	184.2	160	152.8		9,845
190	194.2	40	32.8	16,705	
190	194.2	50	42.8	16,360	
190	194.2	60	52.8	15,925	
190	194.2	70	62.8	15,398	
190	194.2	80	72.8	14,779	
190	194.2	90	82.8		28,708
190	194.2	95	87.8		27,914
190	194.2	100	92.8		27,074
190	194.2	105	97.8		26,188
190	194.2	110	102.8		25,254
190	194.2	115	107.8		24,275
190	194.2	120	112.8		23,249
190	194.2	125	117.8		22,176
190	194.2	130	122.8		21,057
190	194.2	135	127.8		19,891
190	194.2	140	132.8		18,679
190	194.2	145	137.8		17,420
190	194.2	150	142.8		16,115
190	194.2	155	147.8		14,763
190	194.2	160	152.8		13,365
190	194.2	165	157.8		11,920
190	194.2	170	162.8		10,429
200	204.2	40	32.8	18,522	
200	204.2	50	42.8	18,177	
200	204.2	60	52.8	17,741	
200	204.2	70	62.8	17,214	
200	204.2	80	72.8	16,596	
200	204.2	90	82.8	15,886	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
200	204.2	100	92.8	15,086	30,780
200	204.2	105	97.8		29,894
200	204.2	110	102.8	14,194	28,961
200	204.2	115	107.8		27,981
200	204.2	120	112.8		26,955
200	204.2	125	117.8		25,882
200	204.2	130	122.8		24,763
200	204.2	135	127.8		23,598
200	204.2	140	132.8		22,385
200	204.2	145	137.8		21,127
200	204.2	150	142.8		19,821
200	204.2	155	147.8		18,470
200	204.2	160	152.8		17,071
200	204.2	165	157.8		15,627
200	204.2	170	162.8		14,135
200	204.2	175	167.8		12,598
200	204.2	180	172.8		11,013
210	219.0	40	32.8	21,377	
210	219.0	50	42.8	21,033	
210	219.0	60	52.8	20,597	
210	219.0	70	62.8	20,070	
210	219.0	80	72.8	19,451	
210	219.0	90	82.8	18,742	
210	219.0	100	92.8	17,941	
210	219.0	110	102.8	17,050	
220	229.0	40	32.8	23,420	
220	229.0	50	42.8	23,075	
220	229.0	60	52.8	22,639	
220	229.0	70	62.8	22,112	
220	229.0	80	72.8	21,494	
220	229.0	90	82.8	20,785	
220	229.0	100	92.8	19,984	
220	229.0	110	102.8	19,092	
220	229.0	120	112.8	18,109	
230	239.0	40	32.8	25,554	
230	239.0	50	42.8	25,209	
230	239.0	60	52.8	24,773	
230	239.0	70	62.8	24,246	
230	239.0	80	72.8	23,628	
230	239.0	90	82.8	22,918	
230	239.0	100	92.8	22,118	
230	239.0	110	102.8	21,226	
230	239.0	120	112.8	20,243	
230	239.0	130	122.8	19,169	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
240	249.0	40	32.8	27,779	
240	249.0	50	42.8	27,434	
240	249.0	60	52.8	26,998	
240	249.0	70	62.8	26,471	
240	249.0	80	72.8	25,853	
240	249.0	90	82.8	25,143	
240	249.0	100	92.8	24,343	
240	249.0	110	102.8	23,451	
240	249.0	120	112.8	22,468	
240	249.0	130	122.8	21,394	
240	249.0	140	132.8	20,228	
250	259.0	40	32.8	30,095	
250	259.0	50	42.8	29,750	
250	259.0	60	52.8	29,314	
250	259.0	70	62.8	28,787	
250	259.0	80	72.8	28,169	
250	259.0	90	82.8	27,460	
250	259.0	100	92.8	26,659	
250	259.0	110	102.8	25,767	
250	259.0	120	112.8	24,784	
250	259.0	130	122.8	23,710	
250	259.0	140	132.8	22,545	
250	259.0	150	142.8	21,288	
270	279.0	40	28.0	35,134	
270	279.0	50	38.0	34,833	
270	279.0	60	48.0	34,441	
270	279.0	70	58.0	33,958	
270	279.0	80	68.0	33,383	
270	279.0	90	78.0	32,717	
270	279.0	100	88.0	31,961	
270	279.0	110	98.0	31,113	
270	279.0	120	108.0	30,173	
270	279.0	130	118.0	29,143	
270	279.0	140	128.0	28,021	
270	279.0	150	138.0	26,808	
270	279.0	175	163.0	23,377	
275	284.0	40	28.0	36,417	
275	284.0	50	38.0	36,116	
275	284.0	60	48.0	35,724	
275	284.0	70	58.0	35,241	
275	284.0	80	68.0	34,667	
275	284.0	90	78.0	34,001	
275	284.0	100	88.0	33,244	
275	284.0	110	98.0	32,396	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
275	284.0	120	112.8	30,974	
275	284.0	130	122.8	29,899	
275	284.0	140	132.8	28,734	
275	284.0	150	142.8	27,477	
275	284.0	175	167.8	23,937	
280	289.0	40	32.8	37,591	
280	289.0	50	42.8	37,246	
280	289.0	60	52.8	36,810	
280	289.0	70	62.8	36,283	
280	289.0	80	72.8	35,665	
280	289.0	90	82.8	34,955	
280	289.0	100	92.8	34,155	
280	289.0	110	102.8	33,263	
280	289.0	120	112.8	32,280	
280	289.0	130	122.8	31,206	
280	289.0	140	132.8	30,040	
280	289.0	150	142.8	28,784	
280	289.0	175	167.8	25,243	
300	309.0	40	32.8	43,044	
300	309.0	70	62.8	41,736	
300	309.0	80	72.8	41,118	
300	309.0	90	82.8	40,408	
300	309.0	100	92.8	39,608	
300	309.0	110	98.0	39,155	
300	309.0	120	108.0	38,216	
300	309.0	130	118.0	37,186	
300	309.0	140	128.0	36,064	
300	309.0	150	138.0	34,851	
300	309.0	175	163.0	31,420	
300	309.0	200	188.0	27,419	
310	319.0	40	28.0	46,040	
310	319.0	50	38.0	45,739	
310	319.0	60	48.0	45,347	
310	319.0	70	58.0	44,864	
310	319.0	80	68.0	44,289	
310	319.0	90	78.0	43,624	
310	319.0	100	88.0	42,867	
310	319.0	110	98.0	42,019	
310	319.0	120	108.0	41,079	
310	319.0	130	118.0	40,049	
310	319.0	140	128.0	38,927	
310	319.0	150	138.0	37,715	
310	319.0	175	163.0	34,284	
310	319.0	200	188.0	30,283	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Page: 8/11

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
325	334.0	40	32.8	50,373	
325	334.0	50	42.8	50,028	
325	334.0	60	52.8	49,592	
325	334.0	70	62.8	49,065	
325	334.0	80	72.8	48,447	
325	334.0	90	82.8	47,738	
325	334.0	100	92.8	46,937	
325	334.0	110	102.8	46,045	
325	334.0	120	112.8	45,062	
325	334.0	130	122.8	43,988	
325	334.0	140	132.8	42,822	
325	334.0	150	142.8	41,566	
325	334.0	175	167.8	38,026	
325	334.0	200	192.8	33,915	
325	334.0	225	217.8	29,235	
340	349.0	40	32.8	55,044	
340	349.0	50	42.8	54,699	
340	349.0	60	52.8	54,263	
340	349.0	70	62.8	53,736	
340	349.0	80	72.8	53,118	
340	349.0	90	82.8	52,409	
340	349.0	100	92.8	51,608	
340	349.0	110	102.8	50,716	
340	349.0	120	108.0	50,216	
340	349.0	130	118.0	49,186	
340	349.0	140	128.0	48,064	
340	349.0	150	138.0	46,852	
340	349.0	175	163.0	43,421	
340	349.0	200	188.0	39,420	
340	349.0	225	213.0	34,849	
355	364.0	40	28.0	60,053	
355	364.0	50	38.0	59,752	
355	364.0	60	48.0	59,360	
355	364.0	70	58.0	58,877	
355	364.0	80	68.0	58,303	
355	364.0	90	78.0	57,637	
355	364.0	100	88.0	56,880	
355	364.0	110	98.0	56,032	
355	364.0	120	108.0	55,093	
355	364.0	130	118.0	54,062	
355	364.0	140	128.0	52,941	
355	364.0	150	138.0	51,728	
355	364.0	175	163.0	48,297	
355	364.0	200	188.0	44,296	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
355	364.0	225	217.8	38,782	
355	364.0	250	242.8	33,532	
375	384.0	40	32.8	66,741	
375	384.0	50	42.8	66,396	
375	384.0	60	52.8	65,961	
375	384.0	70	62.8	65,433	
375	384.0	80	72.8	64,815	
375	384.0	90	82.8	64,106	
375	384.0	100	92.8	63,305	
375	384.0	110	102.8	62,413	
375	384.0	120	112.8	61,430	
375	384.0	130	122.8	60,356	
375	384.0	140	132.8	59,191	
375	384.0	150	142.8	57,934	
375	384.0	175	167.8	54,394	
375	384.0	200	192.8	50,284	
375	384.0	225	217.8	45,603	
375	384.0	250	242.8	40,353	
400	409.0	40	32.8	75,780	
400	409.0	50	42.8	75,435	
400	409.0	60	52.8	75,000	
400	409.0	70	62.8	74,473	
400	409.0	80	72.8	73,854	
400	409.0	90	82.8	73,145	
400	409.0	100	92.8	72,344	
400	409.0	110	102.8	71,452	
400	409.0	120	112.8	70,469	
400	409.0	130	122.8	69,395	
400	409.0	140	132.8	68,230	
400	409.0	150	142.8	66,973	
400	409.0	175	167.8	63,433	
400	409.0	200	192.8	59,323	
400	409.0	225	217.8	54,642	
400	409.0	250	242.8	49,392	
400	409.0	300	288.0	38,453	
410	419.0	40	32.8	79,555	
410	419.0	50	42.8	79,211	
410	419.0	60	52.8	78,775	
410	419.0	70	62.8	78,248	
410	419.0	80	72.8	77,629	
410	419.0	90	82.8	76,920	
410	419.0	100	92.8	76,119	
410	419.0	110	102.8	75,228	
410	419.0	120	112.8	74,245	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
410	419.0	130	122.8	73,170	
410	419.0	140	132.8	72,005	
410	419.0	150	142.8	70,748	
410	419.0	175	167.8	67,208	
410	419.0	200	192.8	63,098	
410	419.0	225	217.8	58,417	
410	419.0	250	242.8	53,167	
410	419.0	300	292.8	40,957	
430	445.0	70	62.8	88,490	
430	445.0	80	72.8	87,872	
430	445.0	90	82.8	87,162	
430	445.0	100	92.8	86,362	
430	445.0	110	102.8	85,470	
430	445.0	120	112.8	84,487	
430	445.0	130	122.8	83,413	
430	445.0	140	132.8	82,247	
430	445.0	150	142.8	80,991	
430	445.0	175	167.8	77,450	
430	445.0	200	192.8	73,340	
430	445.0	225	217.8	68,660	
430	445.0	250	242.8	63,410	
430	445.0	300	288.0	52,471	
450	465.0	40	32.8	98,096	
450	465.0	70	62.8	96,788	
450	465.0	80	72.8	96,170	
450	465.0	90	82.8	95,460	
450	465.0	100	92.8	94,660	
450	465.0	110	102.8	93,768	
450	465.0	120	112.8	92,785	
450	465.0	140	132.8	90,545	
450	465.0	150	142.8	89,289	
450	465.0	175	167.8	85,748	
450	465.0	200	192.8	81,638	
450	465.0	225	217.8	76,958	
450	465.0	250	238.0	72,760	
450	465.0	300	288.0	60,769	
500	515.0	40	32.8	120,437	
500	515.0	70	62.8	119,129	
500	515.0	80	72.8	118,511	
500	515.0	90	82.8	117,801	
500	515.0	100	92.8	117,001	
500	515.0	110	102.8	116,109	
500	515.0	120	112.8	115,126	
500	515.0	130	122.8	114,052	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
126 - 200	+0, +7
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

LENGHT TOLERANCES	
Lenght mm	Tol. Mm
500	+0, +80
1000	+0, +50

On request, it can be produced in different dimensions.

KESTAMİD® HOLLOW RODS

Page: 11/11

Nominal O. D. mm	Real O. D. mm	Nominal I. D. mm	Real I. D. mm	Weight Gr/Piece	
				Lenght 500 mm	Lenght 1000 mm
500	515.0	140	132.8	112,886	
500	515.0	150	142.8	111,630	
500	515.0	175	167.8	108,089	
500	515.0	200	192.8	103,979	
500	515.0	225	217.8	99,299	
500	515.0	250	242.8	94,049	
500	515.0	300	288.0	83,110	
625	640.0	40	32.8	186,263	
625	640.0	70	62.8	184,956	
625	640.0	80	72.8	184,337	
625	640.0	90	82.8	183,628	
625	640.0	100	92.8	182,827	
625	640.0	110	102.8	181,935	
625	640.0	120	112.8	180,952	
625	640.0	140	132.8	178,713	
625	640.0	150	142.8	177,456	
625	640.0	175	167.8	173,916	
625	640.0	200	192.8	169,806	
625	640.0	225	217.8	165,125	
625	640.0	250	242.8	159,875	
625	640.0	300	288.0	148,936	

TOLERANCES	
O. D. mm	Tol. mm
70 - 125	+0, +5
201 - 410	+0, +15
>410	+0, +25

I. D. mm	Tol. Mm
45 - 250	-0, -12
>250	-0, -20

On request, it can be produced in different dimensions.

KESTAMİD® Polikim's registered trademark