

KESTAMİD® ROD RANGE



DIAMETER	TOLERANCE	LENGTH	
		KG/Length	
(mm)	(mm)	500	1000
(mm)	(mm)	(mm)	(mm)
60		2,00	3,70
65	+0,3/+2,5	2,30	4,31
70		2,70	5,00
75		2,90	5,80
80	+04/+2,8	3,50	6,33
85		3,80	7,14
90	+0,5/+3,2	4,45	8,30
95		X	8,88
100	+0,6/+3,5	5,35	10,00
105		5,85	10,40
110	+0,7/+3,9	6,41	12,45
115		6,62	13,23
120	+0,8/+4,3	7,50	14,27
125		7,98	15,65
130		8,70	16,66
135	+0,8/+5,0	9,75	18,05
140		10,30	19,65
145		10,70	20,85
150	+0,8/+5,3	11,70	22,38
160	+0,8/+6,0	12,50	25,30
165		X	26,52
170	+1/+6,5	15,50	28,80
180		16,40	31,67
185		X	33,50
190		18,20	35,60
195	+1/+7,5	19,35	38,70
200		20,90	39,80

Average production weights listed
 Non-standard items are available on request
 A cut-to-size service available on request

DIAMETER	TOLERANCE	LENGTH	
		KG/Length	
(mm)	(mm)	500	1000
(mm)	(mm)	(mm)	(mm)
210		23,00	43,04
220	+1/+8,5	23,78	49,00
230		26,50	51,00
240	+1/+9,5	29,50	56,10
250		30,80	62,45
260		33,50	66,50
270		36,50	71,40
275	+1/+11,0	39,00	X
280		40,00	76,50
290		X	82,31
300		44,90	88,00
310	+1,5/+12,0	X	X
320		51,00	99,96
330		X	106,08
340		59,00	115,26
350	+1,5/+13,5	X	119,85
360		64,00	125,50
370		X	133,62
375		75,00	X
380	+1,5/+15,0	X	142,80
390		X	147,00
400		82,50	155,21
410		87,00	X
430	+1,5/+16,5	94,50	X
450		103,00	X
500	+3/+21,0	132,00	X

LENGTH TOLERANCE(mm)	
1000	0,+50