

## POM-C SHEET TOLERANCE TABLE



<b>Thickness</b>	<b>tolerances</b>	<b>Width</b>	<b>tolerances</b>	<b>Lenght</b>	<b>tolerances</b>
<i>From 8 to 10 mm</i>	<i>+0,2 mm +1,1 mm</i>	<i>1000 mm</i>	<i>+10 mm +30 mm</i>	<i>2000</i>	<i>+20 mm +60 mm</i>
<i>Over 10 to 25 mm</i>	<i>+0,3 mm +1,7 mm</i>	<i>1000 mm</i>	<i>+10 mm +30 mm</i>	<i>2000</i>	<i>+20 mm +60 mm</i>
<i>Over 25 to 50 mm</i>	<i>+0,5 mm +2,5 mm</i>	<i>1000 mm</i>	<i>+10 mm +30 mm</i>	<i>2000</i>	<i>+20 mm +60 mm</i>
<i>Over 50 to 70 mm</i>	<i>+0,5 mm +3,5 mm</i>	<i>1000 mm</i>	<i>+10 mm +30 mm</i>	<i>2000</i>	<i>+20 mm +60 mm</i>
<i>Over 70 to 100 mm</i>	<i>+0,5 mm +5,0 mm</i>	<i>1000 mm</i>	<i>+10 mm +30 mm</i>	<i>2000</i>	<i>+20 mm +60 mm</i>

## POM-C ROD TOLERANCE TABLE

<b>Outside Diameter</b>	<b>tolerances</b>	<b>Lenght</b>	<b>tolerances</b>
<i>From 10 to 18 mm</i>	<i>+0,2 mm +1,1 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 18 to 30 mm</i>	<i>+0,6mm +2,0 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 30 to 50 mm</i>	<i>+0,6 mm +2,0 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 50 to 60 mm</i>	<i>+0,8 mm +2,5 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 60 to 80 mm</i>	<i>+0,8 mm +3,0 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 80 to 110 mm</i>	<i>+1,0mm +3,6 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 110 to 150 mm</i>	<i>+1,2 mm +4,5 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>
<i>Over 150 to 200 mm</i>	<i>+1,5 mm +5,0 mm</i>	<i>3000 mm</i>	<i>+30 mm +100 mm</i>

**Tolerances comply EN 15860:2010**