

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 40 | 40.9 | 15 | 14.6 | 253 | 380 | 506 |
| 40 | 40.9 | 20 | 19.5 | 223 | 334 | 445 |
| 40 | 40.9 | 25 | 24.4 | 183 | 275 | 366 |
| 45 | 46.0 | 20 | 19.5 | 300 | 450 | 599 |
| 45 | 46.0 | 25 | 24.4 | 261 | 391 | 521 |
| 45 | 46.0 | 30 | 29.3 | 213 | 319 | 425 |
| 50 | 51.1 | 20 | 19.5 | 386 | 579 | 772 |
| 50 | 51.1 | 25 | 24.4 | 347 | 520 | 694 |
| 50 | 51.1 | 30 | 29.3 | 299 | 448 | 598 |
| 50 | 51.1 | 35 | 34.2 | 242 | 363 | 484 |
| 55 | 56.2 | 20 | 19.5 | 482 | 723 | 963 |
| 55 | 56.2 | 25 | 24.4 | 443 | 664 | 885 |
| 55 | 56.2 | 30 | 29.3 | 395 | 592 | 789 |
| 55 | 56.2 | 35 | 34.2 | 338 | 507 | 675 |
| 55 | 56.2 | 40 | 39.1 | 272 | 408 | 544 |
| 60 | 61.3 | 20 | 19.5 | 586 | 879 | 1,172 |
| 60 | 61.3 | 25 | 24.4 | 547 | 821 | 1,094 |
| 60 | 61.3 | 30 | 29.3 | 499 | 749 | 998 |
| 60 | 61.3 | 35 | 34.2 | 443 | 664 | 885 |
| 60 | 61.3 | 40 | 39.1 | 377 | 565 | 754 |
| 60 | 61.3 | 45 | 44.0 | 303 | 454 | 605 |
| 65 | 66.4 | 20 | 19.5 | 700 | 1,050 | 1,400 |
| 65 | 66.4 | 25 | 24.4 | 661 | 991 | 1,321 |
| 65 | 66.4 | 30 | 29.3 | 613 | 919 | 1,225 |
| 65 | 66.4 | 35 | 34.2 | 556 | 834 | 1,112 |
| 65 | 66.4 | 40 | 39.1 | 491 | 736 | 981 |
| 65 | 66.4 | 45 | 44.0 | 417 | 625 | 833 |
| 65 | 66.4 | 50 | 48.9 | 334 | 500 | 667 |
| 70 | 71.5 | 25 | 24.4 | 784 | 1,175 | 1,567 |
| 70 | 71.5 | 30 | 29.3 | 736 | 1,103 | 1,471 |
| 70 | 71.5 | 35 | 34.2 | 679 | 1,018 | 1,357 |
| 70 | 71.5 | 40 | 39.1 | 613 | 920 | 1,226 |
| 70 | 71.5 | 45 | 44.0 | 539 | 809 | 1,078 |
| 70 | 71.5 | 50 | 48.9 | 456 | 684 | 912 |
| 70 | 71.5 | 55 | 53.8 | 365 | 547 | 729 |
| 75 | 76.6 | 30 | 29.3 | 867 | 1,301 | 1,734 |
| 75 | 76.6 | 35 | 34.2 | 811 | 1,216 | 1,621 |
| 75 | 76.6 | 40 | 39.1 | 745 | 1,118 | 1,490 |
| 75 | 76.6 | 45 | 44.0 | 671 | 1,006 | 1,342 |
| 75 | 76.6 | 50 | 48.9 | 588 | 882 | 1,176 |
| 75 | 76.6 | 55 | 53.8 | 497 | 745 | 993 |
| 75 | 76.6 | 60 | 58.7 | 396 | 594 | 792 |
| 80 | 81.7 | 30 | 29.3 | 1,008 | 1,512 | 2,016 |
| 80 | 81.7 | 35 | 34.2 | 952 | 1,427 | 1,903 |
| 80 | 81.7 | 40 | 39.1 | 886 | 1,329 | 1,772 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 80 | 81.7 | 45 | 44.0 | 812 | 1,218 | 1,624 |
| 80 | 81.7 | 50 | 48.9 | 729 | 1,093 | 1,458 |
| 80 | 81.7 | 55 | 53.8 | 637 | 956 | 1,274 |
| 80 | 81.7 | 60 | 58.7 | 537 | 805 | 1,074 |
| 80 | 81.7 | 65 | 63.6 | 428 | 642 | 856 |
| 85 | 86.8 | 30 | 29.3 | 1,158 | 1,737 | 2,316 |
| 85 | 86.8 | 35 | 34.2 | 1,102 | 1,652 | 2,203 |
| 85 | 86.8 | 40 | 39.1 | 1,036 | 1,554 | 2,072 |
| 85 | 86.8 | 45 | 44.0 | 962 | 1,443 | 1,923 |
| 85 | 86.8 | 50 | 48.9 | 879 | 1,318 | 1,758 |
| 85 | 86.8 | 55 | 53.8 | 787 | 1,181 | 1,574 |
| 85 | 86.8 | 60 | 58.7 | 687 | 1,030 | 1,374 |
| 85 | 86.8 | 65 | 63.6 | 578 | 867 | 1,156 |
| 85 | 86.8 | 70 | 68.5 | 460 | 690 | 920 |
| 90 | 91.9 | 35 | 34.2 | 1,261 | 1,891 | 2,521 |
| 90 | 91.9 | 40 | 39.1 | 1,195 | 1,793 | 2,390 |
| 90 | 91.9 | 45 | 44.0 | 1,121 | 1,681 | 2,242 |
| 90 | 91.9 | 50 | 48.9 | 1,038 | 1,557 | 2,076 |
| 90 | 91.9 | 55 | 53.8 | 947 | 1,420 | 1,893 |
| 90 | 91.9 | 60 | 58.7 | 846 | 1,269 | 1,692 |
| 90 | 91.9 | 65 | 63.6 | 737 | 1,105 | 1,474 |
| 90 | 91.9 | 70 | 68.5 | 619 | 929 | 1,238 |
| 90 | 91.9 | 75 | 73.4 | 493 | 739 | 985 |
| 95 | 97.0 | 40 | 39.1 | 1,363 | 2,045 | 2,726 |
| 95 | 97.0 | 45 | 44.0 | 1,289 | 1,934 | 2,578 |
| 95 | 97.0 | 50 | 48.9 | 1,206 | 1,809 | 2,412 |
| 95 | 97.0 | 55 | 53.8 | 1,115 | 1,672 | 2,229 |
| 95 | 97.0 | 60 | 58.7 | 1,014 | 1,521 | 2,028 |
| 95 | 97.0 | 65 | 63.6 | 905 | 1,358 | 1,810 |
| 95 | 97.0 | 70 | 68.5 | 787 | 1,181 | 1,574 |
| 95 | 97.0 | 75 | 73.4 | 661 | 991 | 1,321 |
| 95 | 97.0 | 80 | 78.3 | 526 | 788 | 1,051 |
| 100 | 102.1 | 40 | 39.1 | 1,541 | 2,311 | 3,081 |
| 100 | 102.1 | 45 | 44.0 | 1,466 | 2,199 | 2,932 |
| 100 | 102.1 | 50 | 48.9 | 1,383 | 2,075 | 2,766 |
| 100 | 102.1 | 55 | 53.8 | 1,292 | 1,938 | 2,583 |
| 100 | 102.1 | 60 | 58.7 | 1,192 | 1,787 | 2,383 |
| 100 | 102.1 | 65 | 63.6 | 1,082 | 1,623 | 2,164 |
| 100 | 102.1 | 70 | 68.5 | 965 | 1,447 | 1,929 |
| 100 | 102.1 | 75 | 73.4 | 838 | 1,257 | 1,676 |
| 100 | 102.1 | 80 | 78.3 | 703 | 1,054 | 1,405 |
| 100 | 102.1 | 85 | 83.2 | 559 | 838 | 1,117 |
| 120 | 122.6 | 40 | 39.1 | 2,344 | 3,516 | 4,688 |
| 120 | 122.6 | 45 | 44.0 | 2,270 | 3,405 | 4,540 |
| 120 | 122.6 | 50 | 48.9 | 2,187 | 3,281 | 4,374 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 120 | 122.9 | 55 | 53.6 | 2,109 | 3,163 | 4,217 |
| 120 | 122.9 | 60 | 58.5 | 2,008 | 3,012 | 4,016 |
| 120 | 122.9 | 65 | 63.4 | 1,899 | 2,849 | 3,798 |
| 120 | 122.9 | 70 | 68.3 | 1,781 | 2,672 | 3,562 |
| 120 | 122.9 | 75 | 73.2 | 1,655 | 2,482 | 3,309 |
| 120 | 122.9 | 80 | 78.0 | 1,520 | 2,279 | 3,039 |
| 120 | 122.9 | 85 | 82.9 | 1,376 | 2,063 | 2,751 |
| 120 | 122.9 | 90 | 87.8 | 1,223 | 1,834 | 2,445 |
| 120 | 122.9 | 95 | 92.7 | 1,061 | 1,592 | 2,122 |
| 120 | 122.9 | 100 | 97.6 | 891 | 1,337 | 1,782 |
| 125 | 128.0 | 30 | 29.2 | 2,703 | 4,054 | 5,405 |
| 125 | 128.0 | 35 | 34.1 | 2,646 | 3,969 | 5,292 |
| 125 | 128.0 | 40 | 39.0 | 2,581 | 3,871 | 5,161 |
| 125 | 128.0 | 45 | 43.9 | 2,506 | 3,759 | 5,012 |
| 125 | 128.0 | 50 | 48.8 | 2,424 | 3,635 | 4,847 |
| 125 | 128.0 | 55 | 53.6 | 2,332 | 3,498 | 4,663 |
| 125 | 128.0 | 60 | 58.5 | 2,232 | 3,347 | 4,463 |
| 125 | 128.0 | 65 | 63.4 | 2,123 | 3,184 | 4,245 |
| 125 | 128.0 | 70 | 68.3 | 2,005 | 3,007 | 4,009 |
| 125 | 128.0 | 75 | 73.2 | 1,878 | 2,817 | 3,756 |
| 125 | 128.0 | 80 | 78.0 | 1,743 | 2,614 | 3,485 |
| 125 | 128.0 | 85 | 82.9 | 1,599 | 2,398 | 3,197 |
| 125 | 128.0 | 90 | 87.8 | 1,446 | 2,169 | 2,892 |
| 125 | 128.0 | 95 | 92.7 | 1,285 | 1,927 | 2,569 |
| 125 | 128.0 | 100 | 97.6 | 1,115 | 1,672 | 2,229 |
| 125 | 128.0 | 105 | 102.4 | 936 | 1,403 | 1,871 |
| 130 | 133.2 | 30 | 29.2 | 2,940 | 4,410 | 5,879 |
| 130 | 133.2 | 35 | 34.1 | 2,883 | 4,324 | 5,766 |
| 130 | 133.2 | 40 | 39.0 | 2,818 | 4,226 | 5,635 |
| 130 | 133.2 | 45 | 43.9 | 2,744 | 4,115 | 5,487 |
| 130 | 133.2 | 50 | 48.8 | 2,661 | 3,991 | 5,321 |
| 130 | 133.2 | 55 | 53.6 | 2,569 | 3,853 | 5,137 |
| 130 | 133.2 | 60 | 58.5 | 2,469 | 3,703 | 4,937 |
| 130 | 133.2 | 65 | 63.4 | 2,360 | 3,539 | 4,719 |
| 130 | 133.2 | 70 | 68.3 | 2,242 | 3,362 | 4,483 |
| 130 | 133.2 | 75 | 73.2 | 2,115 | 3,173 | 4,230 |
| 130 | 133.2 | 80 | 78.0 | 1,980 | 2,970 | 3,959 |
| 130 | 133.2 | 85 | 82.9 | 1,836 | 2,754 | 3,671 |
| 130 | 133.2 | 90 | 87.8 | 1,683 | 2,525 | 3,366 |
| 130 | 133.2 | 95 | 92.7 | 1,522 | 2,283 | 3,043 |
| 130 | 133.2 | 100 | 97.6 | 1,352 | 2,027 | 2,703 |
| 130 | 133.2 | 105 | 102.4 | 1,173 | 1,759 | 2,345 |
| 130 | 133.2 | 110 | 107.3 | 985 | 1,478 | 1,970 |
| 135 | 138.3 | 50 | 48.8 | 2,902 | 4,353 | 5,804 |
| 135 | 138.3 | 55 | 53.6 | 2,811 | 4,216 | 5,621 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 135 | 137.9 | 60 | 58.7 | 2,691 | 4,036 | 5,382 |
| 135 | 137.9 | 65 | 63.6 | 2,582 | 3,873 | 5,163 |
| 135 | 137.9 | 70 | 68.5 | 2,464 | 3,696 | 4,928 |
| 135 | 137.9 | 75 | 73.4 | 2,338 | 3,506 | 4,675 |
| 135 | 137.9 | 80 | 78.3 | 2,202 | 3,303 | 4,404 |
| 135 | 137.9 | 85 | 83.2 | 2,058 | 3,087 | 4,116 |
| 135 | 137.9 | 90 | 88.1 | 1,906 | 2,858 | 3,811 |
| 135 | 137.9 | 100 | 97.9 | 1,574 | 2,361 | 3,148 |
| 135 | 137.9 | 110 | 107.6 | 1,208 | 1,811 | 2,415 |
| 140 | 143.0 | 30 | 29.3 | 3,412 | 5,118 | 6,824 |
| 140 | 143.0 | 35 | 34.2 | 3,356 | 5,033 | 6,711 |
| 140 | 143.0 | 40 | 39.1 | 3,290 | 4,935 | 6,580 |
| 140 | 143.0 | 45 | 44.0 | 3,216 | 4,824 | 6,431 |
| 140 | 143.0 | 50 | 48.9 | 3,133 | 4,699 | 6,265 |
| 140 | 143.0 | 55 | 53.8 | 3,041 | 4,562 | 6,082 |
| 140 | 143.0 | 60 | 58.7 | 2,941 | 4,411 | 5,882 |
| 140 | 143.0 | 65 | 63.6 | 2,832 | 4,248 | 5,663 |
| 140 | 143.0 | 70 | 68.5 | 2,714 | 4,071 | 5,428 |
| 140 | 143.0 | 75 | 73.4 | 2,588 | 3,881 | 5,175 |
| 140 | 143.0 | 80 | 78.3 | 2,452 | 3,678 | 4,904 |
| 140 | 143.0 | 85 | 83.2 | 2,308 | 3,462 | 4,616 |
| 140 | 143.0 | 90 | 88.1 | 2,156 | 3,233 | 4,311 |
| 140 | 143.0 | 100 | 97.9 | 1,824 | 2,736 | 3,648 |
| 140 | 143.0 | 105 | 102.7 | 1,645 | 2,468 | 3,290 |
| 140 | 143.0 | 110 | 107.6 | 1,458 | 2,186 | 2,915 |
| 140 | 143.0 | 120 | 117.4 | 1,056 | 1,584 | 2,112 |
| 150 | 153.2 | 50 | 48.9 | 3,660 | 5,490 | 7,320 |
| 150 | 153.2 | 55 | 53.8 | 3,569 | 5,353 | 7,137 |
| 150 | 153.2 | 60 | 58.7 | 3,468 | 5,202 | 6,936 |
| 150 | 153.2 | 65 | 63.6 | 3,359 | 5,039 | 6,718 |
| 150 | 153.2 | 70 | 68.5 | 3,241 | 4,862 | 6,482 |
| 150 | 153.2 | 75 | 73.4 | 3,115 | 4,672 | 6,229 |
| 150 | 153.2 | 80 | 78.3 | 2,980 | 4,469 | 5,959 |
| 150 | 153.2 | 85 | 83.2 | 2,836 | 4,253 | 5,671 |
| 150 | 153.2 | 90 | 88.1 | 2,683 | 4,024 | 5,365 |
| 150 | 153.2 | 100 | 97.9 | 2,351 | 3,527 | 4,702 |
| 150 | 153.2 | 110 | 107.6 | 1,985 | 2,977 | 3,969 |
| 150 | 153.2 | 120 | 117.4 | 1,583 | 2,375 | 3,166 |
| 150 | 153.2 | 125 | 122.3 | 1,370 | 2,054 | 2,739 |
| 150 | 153.2 | 130 | 127.2 | 1,147 | 1,720 | 2,294 |
| 160 | 163.4 | 50 | 48.9 | 4,224 | 6,336 | 8,447 |
| 160 | 163.4 | 55 | 53.8 | 4,132 | 6,198 | 8,264 |
| 160 | 163.4 | 60 | 58.7 | 4,032 | 6,048 | 8,063 |
| 160 | 163.4 | 65 | 63.6 | 3,923 | 5,884 | 7,845 |
| 160 | 163.4 | 70 | 68.5 | 3,805 | 5,707 | 7,610 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 160 | 163.4 | 75 | 73.4 | 3,678 | 5,517 | 7,356 |
| 160 | 163.4 | 80 | 78.3 | 3,529 | 5,315 | 7,086 |
| 160 | 163.4 | 90 | 88.1 | 3,234 | 4,870 | 6,493 |
| 160 | 163.4 | 100 | 97.9 | 2,904 | 4,372 | 5,829 |
| 160 | 163.4 | 110 | 107.6 | 2,538 | 3,822 | 5,096 |
| 160 | 163.4 | 120 | 117.4 | 2,139 | 3,220 | 4,294 |
| 160 | 163.4 | 130 | 127.2 | 1,704 | 2,566 | 3,421 |
| 160 | 163.4 | 140 | 137.0 | 1,235 | 1,859 | 2,479 |
| 170 | 173.6 | 50 | 48.9 | 4,805 | 7,235 | 9,647 |
| 170 | 173.6 | 55 | 53.8 | 4,714 | 7,098 | 9,464 |
| 170 | 173.6 | 60 | 58.7 | 4,614 | 6,947 | 9,263 |
| 170 | 173.6 | 65 | 63.6 | 4,505 | 6,784 | 9,045 |
| 170 | 173.6 | 70 | 68.5 | 4,388 | 6,607 | 8,809 |
| 170 | 173.6 | 75 | 73.4 | 4,262 | 6,417 | 8,556 |
| 170 | 173.6 | 80 | 78.3 | 4,127 | 6,214 | 8,286 |
| 170 | 173.6 | 85 | 83.2 | 3,984 | 5,998 | 7,998 |
| 170 | 173.6 | 90 | 88.1 | 3,831 | 5,769 | 7,692 |
| 170 | 173.6 | 100 | 97.9 | 3,501 | 5,272 | 7,029 |
| 170 | 173.6 | 110 | 107.6 | 3,136 | 4,722 | 6,296 |
| 170 | 173.6 | 120 | 117.4 | 2,736 | 4,120 | 5,493 |
| 170 | 173.6 | 125 | 122.3 | 2,523 | 3,799 | 5,066 |
| 170 | 173.6 | 130 | 127.2 | 2,302 | 3,466 | 4,621 |
| 170 | 173.6 | 140 | 137.0 | 1,832 | 2,759 | 3,678 |
| 170 | 173.6 | 150 | 146.8 | 1,328 | 2,000 | 2,666 |
| 175 | 178.7 | 50 | 48.9 | 5,117 | 7,706 | 10,274 |
| 175 | 178.7 | 55 | 53.8 | 5,026 | 7,568 | 10,091 |
| 175 | 178.7 | 60 | 58.7 | 4,926 | 7,418 | 9,890 |
| 175 | 178.7 | 65 | 63.6 | 4,817 | 7,254 | 9,672 |
| 175 | 178.7 | 70 | 68.5 | 4,700 | 7,077 | 9,436 |
| 175 | 178.7 | 75 | 73.4 | 4,574 | 6,888 | 9,183 |
| 175 | 178.7 | 80 | 78.3 | 4,439 | 6,685 | 8,913 |
| 175 | 178.7 | 85 | 83.2 | 4,296 | 6,469 | 8,625 |
| 175 | 178.7 | 90 | 88.1 | 4,144 | 6,240 | 8,320 |
| 175 | 178.7 | 95 | 93.0 | 3,983 | 5,998 | 7,997 |
| 175 | 178.7 | 100 | 97.9 | 3,813 | 5,742 | 7,656 |
| 175 | 178.7 | 110 | 107.6 | 3,448 | 5,193 | 6,923 |
| 175 | 178.7 | 125 | 122.3 | 2,836 | 4,270 | 5,693 |
| 175 | 178.7 | 135 | 132.1 | 2,384 | 3,589 | 4,785 |
| 175 | 178.7 | 140 | 137.0 | 2,145 | 3,229 | 4,306 |
| 175 | 178.7 | 150 | 146.8 | 1,640 | 2,470 | 3,293 |
| 180 | 183.8 | 50 | 48.9 | 5,439 | 8,190 | 10,919 |
| 180 | 183.8 | 55 | 53.8 | 5,347 | 8,052 | 10,736 |
| 180 | 183.8 | 60 | 58.7 | 5,247 | 7,902 | 10,536 |
| 180 | 183.8 | 65 | 63.6 | 5,139 | 7,738 | 10,317 |
| 180 | 183.8 | 70 | 68.5 | 5,021 | 7,561 | 10,082 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 180 | 183.8 | 75 | 73.4 | 4,915 | 7,372 | 9,829 |
| 180 | 183.8 | 80 | 78.3 | 4,779 | 7,169 | 9,558 |
| 180 | 183.8 | 85 | 83.2 | 4,635 | 6,953 | 9,270 |
| 180 | 183.8 | 90 | 88.1 | 4,483 | 6,724 | 8,965 |
| 180 | 183.8 | 100 | 97.9 | 4,151 | 6,226 | 8,302 |
| 180 | 183.8 | 110 | 107.6 | 3,785 | 5,677 | 7,569 |
| 180 | 183.8 | 120 | 117.4 | 3,383 | 5,074 | 6,766 |
| 180 | 183.8 | 125 | 122.3 | 3,169 | 4,754 | 6,338 |
| 180 | 183.8 | 135 | 132.1 | 2,716 | 4,073 | 5,431 |
| 180 | 183.8 | 150 | 146.8 | 1,970 | 2,954 | 3,939 |
| 180 | 183.8 | 160 | 156.6 | 1,429 | 2,143 | 2,857 |
| 190 | 194.0 | 50 | 48.9 | 6,133 | 9,199 | 12,265 |
| 190 | 194.0 | 60 | 58.7 | 5,941 | 8,911 | 11,881 |
| 190 | 194.0 | 75 | 73.4 | 5,587 | 8,380 | 11,174 |
| 190 | 194.0 | 90 | 88.1 | 5,155 | 7,733 | 10,310 |
| 190 | 194.0 | 100 | 97.9 | 4,824 | 7,235 | 9,647 |
| 190 | 194.0 | 110 | 107.6 | 4,457 | 6,685 | 8,914 |
| 190 | 194.0 | 125 | 122.3 | 3,842 | 5,763 | 7,683 |
| 190 | 194.0 | 135 | 132.1 | 3,388 | 5,082 | 6,776 |
| 190 | 194.0 | 150 | 146.8 | 2,642 | 3,963 | 5,284 |
| 190 | 194.0 | 160 | 156.6 | 2,101 | 3,151 | 4,202 |
| 190 | 194.0 | 170 | 166.4 | 1,525 | 2,287 | 3,050 |
| 200 | 204.2 | 50 | 48.9 | 6,841 | 10,262 | 13,682 |
| 200 | 204.2 | 75 | 73.4 | 6,296 | 9,444 | 12,591 |
| 200 | 204.2 | 100 | 97.9 | 5,532 | 8,298 | 11,064 |
| 200 | 204.2 | 110 | 107.6 | 5,166 | 7,749 | 10,331 |
| 200 | 204.2 | 125 | 122.3 | 4,551 | 6,826 | 9,101 |
| 200 | 204.2 | 140 | 137.0 | 3,857 | 5,785 | 7,714 |
| 200 | 204.2 | 150 | 146.8 | 3,351 | 5,026 | 6,701 |
| 200 | 204.2 | 160 | 156.6 | 2,810 | 4,215 | 5,619 |
| 200 | 204.2 | 175 | 171.3 | 1,933 | 2,899 | 3,865 |
| 225 | 229.8 | 50 | 48.9 | 8,780 | 13,170 | 17,560 |
| 225 | 229.8 | 75 | 73.4 | 8,235 | 12,352 | 16,469 |
| 225 | 229.8 | 90 | 88.1 | 7,803 | 11,704 | 15,606 |
| 225 | 229.8 | 100 | 97.9 | 7,471 | 11,207 | 14,942 |
| 225 | 229.8 | 125 | 122.3 | 6,490 | 9,734 | 12,979 |
| 225 | 229.8 | 150 | 146.8 | 5,290 | 7,935 | 10,579 |
| 225 | 229.8 | 160 | 156.6 | 4,749 | 7,123 | 9,497 |
| 225 | 229.8 | 175 | 171.3 | 3,872 | 5,808 | 7,743 |
| 225 | 229.8 | 190 | 186.0 | 2,916 | 4,374 | 5,832 |
| 225 | 229.8 | 200 | 195.8 | 2,236 | 3,353 | 4,471 |
| 250 | 255.3 | 50 | 48.9 | 10,939 | 16,409 | 21,878 |
| 250 | 255.3 | 75 | 73.4 | 10,394 | 15,591 | 20,787 |
| 250 | 255.3 | 100 | 97.9 | 9,630 | 14,445 | 19,260 |
| 250 | 255.3 | 125 | 122.3 | 8,649 | 12,973 | 17,297 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 250 | 255.3 | 150 | 146.8 | 7,449 | 11,173 | 14,897 |
| 250 | 255.3 | 160 | 156.6 | 6,908 | 10,361 | 13,815 |
| 250 | 255.3 | 175 | 171.3 | 6,031 | 9,046 | 12,061 |
| 250 | 255.3 | 190 | 186.0 | 5,075 | 7,613 | 10,150 |
| 250 | 255.3 | 200 | 195.8 | 4,395 | 6,592 | 8,789 |
| 250 | 255.3 | 220 | 215.3 | 2,929 | 4,393 | 5,857 |
| 250 | 255.3 | 225 | 220.2 | 2,540 | 3,810 | 5,080 |
| 255 | 260.4 | 180 | 176.2 | 6,180 | 9,270 | 12,360 |
| 275 | 280.8 | 75 | 73.4 | 12,780 | 19,169 | 25,559 |
| 275 | 280.8 | 100 | 97.9 | 12,016 | 18,024 | 24,032 |
| 275 | 280.8 | 125 | 122.3 | 11,034 | 16,551 | 22,068 |
| 275 | 280.8 | 150 | 146.8 | 9,835 | 14,752 | 19,669 |
| 275 | 280.8 | 160 | 156.6 | 9,294 | 13,940 | 18,587 |
| 275 | 280.8 | 175 | 171.3 | 8,417 | 12,625 | 16,833 |
| 275 | 280.8 | 190 | 186.0 | 7,461 | 11,191 | 14,922 |
| 275 | 280.8 | 200 | 195.8 | 6,780 | 10,170 | 13,560 |
| 275 | 280.8 | 220 | 215.3 | 5,314 | 7,971 | 10,628 |
| 275 | 280.8 | 225 | 220.2 | 4,926 | 7,389 | 9,852 |
| 275 | 280.8 | 250 | 244.7 | 2,854 | 4,280 | 5,707 |
| 300 | 306.3 | 50 | 48.9 | 15,938 | 23,906 | 31,875 |
| 300 | 306.3 | 75 | 73.4 | 15,392 | 23,088 | 30,784 |
| 300 | 306.3 | 100 | 97.9 | 14,629 | 21,943 | 29,257 |
| 300 | 306.3 | 125 | 122.3 | 13,647 | 20,471 | 27,294 |
| 300 | 306.3 | 150 | 146.8 | 12,447 | 18,671 | 24,894 |
| 300 | 306.3 | 160 | 156.6 | 11,906 | 17,859 | 23,812 |
| 300 | 306.3 | 175 | 171.3 | 11,029 | 16,544 | 22,058 |
| 300 | 306.3 | 190 | 186.0 | 10,074 | 15,111 | 20,147 |
| 300 | 306.3 | 200 | 195.8 | 9,393 | 14,090 | 18,786 |
| 300 | 306.3 | 225 | 220.2 | 7,539 | 11,308 | 15,077 |
| 300 | 306.3 | 250 | 244.7 | 5,466 | 8,199 | 10,932 |
| 300 | 306.3 | 270 | 264.3 | 3,651 | 5,477 | 7,302 |
| 325 | 331.9 | 100 | 97.9 | 17,480 | 26,220 | 34,960 |
| 325 | 331.9 | 125 | 122.3 | 16,499 | 24,748 | 32,997 |
| 325 | 331.9 | 150 | 146.8 | 15,299 | 22,948 | 30,597 |
| 325 | 331.9 | 175 | 171.3 | 13,881 | 20,821 | 27,761 |
| 325 | 331.9 | 200 | 195.8 | 12,245 | 18,367 | 24,489 |
| 325 | 331.9 | 225 | 220.2 | 10,390 | 15,585 | 20,780 |
| 325 | 331.9 | 250 | 244.7 | 8,318 | 12,476 | 16,635 |
| 325 | 331.9 | 270 | 264.3 | 6,503 | 9,754 | 13,005 |
| 325 | 331.9 | 300 | 293.7 | 3,518 | 5,277 | 7,036 |
| 355 | 362.5 | 275 | 269.2 | 9,736 | 14,603 | 19,471 |
| 375 | 382.9 | 100 | 97.9 | 23,842 | 35,763 | 47,684 |
| 375 | 382.9 | 125 | 122.3 | 22,861 | 34,291 | 45,721 |
| 375 | 382.9 | 150 | 146.8 | 21,661 | 32,491 | 43,321 |
| 375 | 382.9 | 175 | 171.3 | 20,243 | 30,364 | 40,485 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

| Nominal O.D. mm | Real O.D. mm | Nominal I.D. mm | Real I.D. mm | Weight Gr/Pcs | | |
|-----------------------|--------------------|-----------------------|--------------------|---------------|--------|--------|
| | | | | Height | Height | Height |
| | | | | 100 mm | 150 mm | 200 mm |
| 375 | 382.9 | 200 | 195.8 | 18,607 | 27,910 | 37,213 |
| 375 | 382.9 | 225 | 220.2 | 16,752 | 25,128 | 33,504 |
| 375 | 382.9 | 250 | 244.7 | 14,680 | 22,020 | 29,359 |
| 375 | 382.9 | 270 | 264.3 | 12,865 | 19,297 | 25,729 |
| 375 | 382.9 | 300 | 293.7 | 9,881 | 14,821 | 19,761 |
| 375 | 382.9 | 325 | 318.1 | 7,154 | 10,730 | 14,307 |
| 400 | 408.4 | 100 | 97.9 | 27,364 | 41,046 | 54,727 |
| 400 | 408.4 | 150 | 146.8 | 25,182 | 37,773 | 50,364 |
| 400 | 408.4 | 200 | 195.8 | 22,128 | 33,192 | 44,256 |
| 400 | 408.4 | 250 | 244.7 | 18,202 | 27,302 | 36,403 |
| 400 | 408.4 | 270 | 264.3 | 16,386 | 24,579 | 32,772 |
| 400 | 408.4 | 300 | 293.7 | 13,402 | 20,103 | 26,804 |
| 400 | 408.4 | 325 | 318.1 | 10,675 | 16,013 | 21,350 |
| 400 | 408.4 | 370 | 362.2 | 5,217 | 7,825 | 10,434 |
| 425 | 434.0 | 100 | 97.9 | 31,128 | 46,691 | 62,255 |
| 425 | 434.0 | 150 | 146.8 | 28,946 | 43,419 | 57,892 |
| 425 | 434.0 | 175 | 171.3 | 27,528 | 41,292 | 55,056 |
| 425 | 434.0 | 200 | 195.8 | 25,892 | 38,838 | 51,783 |
| 425 | 434.0 | 225 | 220.2 | 24,038 | 36,056 | 48,075 |
| 425 | 434.0 | 250 | 244.7 | 21,965 | 32,947 | 43,930 |
| 425 | 434.0 | 270 | 264.3 | 20,150 | 30,225 | 40,300 |
| 425 | 434.0 | 305 | 298.5 | 16,638 | 24,957 | 33,275 |
| 425 | 434.0 | 325 | 318.1 | 14,439 | 21,658 | 28,877 |
| 425 | 434.0 | 370 | 362.2 | 8,981 | 13,471 | 17,961 |

| TOLERANCES | |
|------------|-----------|
| O.D. | +%3.5, -0 |
| I.D. | +%3.5, -0 |
| Height | +%4, -0 |

On request, it can be produced in different dimensions.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|--------------|
| 440 | 90 | 344 |
| 440 | 200 | 290 |
| 440 | 255 | 244 |
| 440 | 320 | 179 |
| 440 | 340 | 157 |
| 440 | 345 | 148 |
| 440 | 360 | 134 |
| 440 | 3720 | 120 |
| 440 | 385 | 101 |
| 440 | 390 | 94 |
| 440 | 400 | 74 |
| 440 | 410 | 60 |
| 450 | 100 | 356 |
| 450 | 215 | 300 |
| 450 | 315 | 207 |
| 450 | 335 | 185 |
| 450 | 340 | 175 |
| 450 | 360 | 156 |
| 450 | 370 | 142 |
| 450 | 385 | 123 |
| 450 | 400 | 96 |
| 450 | 410 | 62 |
| 450 | 425 | 59 |
| 465 | 170 | 347 |
| 465 | 290 | 251 |
| 465 | 315 | 225 |
| 465 | 335 | 202 |
| 465 | 345 | 188 |
| 465 | 360 | 174 |
| 465 | 385 | 141 |
| 465 | 390 | 134 |
| 465 | 400 | 114 |
| 465 | 410 | 100 |
| 465 | 425 | 78 |
| 465 | 445 | 48 |
| 480 | 230 | 331 |
| 480 | 335 | 227 |
| 480 | 345 | 213 |
| 480 | 360 | 199 |
| 480 | 385 | 166 |
| 480 | 390 | 159 |
| 480 | 400 | 139 |
| 480 | 410 | 125 |
| 480 | 425 | 101 |
| 480 | 445 | 73 |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|-----------------|
| 480 | 460 | 49 |
| 490 | 320 | 261 |
| 490 | 360 | 216 |
| 490 | 385 | 183 |
| 490 | 400 | 156 |
| 490 | 410 | 142 |
| 490 | 425 | 118 |
| 490 | 445 | 90 |
| 490 | 460 | 66 |
| 500 | 305 | 304 |
| 500 | 345 | 257 |
| 500 | 385 | 209 |
| 500 | 400 | 182 |
| 500 | 410 | 168 |
| 500 | 425 | 145 |
| 500 | 445 | 116 |
| 500 | 460 | 93 |
| 500 | 475 | 68 |
| 515 | 110 | 473 |
| 515 | 285 | 351 |
| 515 | 335 | 298 |
| 515 | 400 | 209 |
| 515 | 410 | 195 |
| 515 | 425 | 172 |
| 515 | 445 | 143 |
| 515 | 460 | 120 |
| 515 | 475 | 95 |
| 515 | 485 | 77 |
| 530 | 385 | 264 |
| 530 | 425 | 200 |
| 530 | 445 | 171 |
| 530 | 460 | 147 |
| 530 | 475 | 123 |
| 530 | 485 | 105 |
| 530 | 505 | 74 |
| 545 | 145 | 510 |
| 545 | 360 | 326 |
| 545 | 388 | 292 |
| 545 | 400 | 265 |
| 545 | 410 | 251 |
| 545 | 425 | 228 |
| 545 | 445 | 199 |
| 545 | 460 | 176 |
| 545 | 475 | 152 |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|-----------------|
| 545 | 485 | 113 |
| 545 | 495 | 117 |
| 545 | 505 | 103 |
| 545 | 515 | 83 |
| 560 | 290 | 429 |
| 560 | 320 | 398 |
| 560 | 400 | 293 |
| 560 | 425 | 255 |
| 560 | 445 | 227 |
| 560 | 460 | 203 |
| 560 | 475 | 179 |
| 560 | 495 | 161 |
| 560 | 505 | 130 |
| 560 | 515 | 111 |
| 560 | 530 | 84 |
| 560 | 540 | 65 |
| 570 | 220 | 523 |
| 570 | 250 | 499 |
| 570 | 360 | 385 |
| 570 | 445 | 259 |
| 570 | 485 | 193 |
| 570 | 495 | 176 |
| 570 | 505 | 162 |
| 570 | 515 | 143 |
| 570 | 530 | 116 |
| 570 | 540 | 97 |
| 590 | 390 | 386 |
| 590 | 400 | 366 |
| 590 | 410 | 352 |
| 590 | 475 | 252 |
| 590 | 485 | 234 |
| 590 | 505 | 203 |
| 590 | 515 | 184 |
| 590 | 530 | 157 |
| 590 | 540 | 139 |
| 590 | 560 | 101 |
| 610 | 390 | 429 |
| 610 | 415 | 395 |
| 610 | 430 | 371 |
| 610 | 445 | 343 |
| 610 | 460 | 319 |
| 610 | 470 | 303 |
| 610 | 475 | 295 |
| 610 | 485 | 277 |
| 610 | 505 | 246 |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|-----------------|
| 610 | 515 | 227 |
| 610 | 530 | 200 |
| 610 | 540 | 181 |
| 610 | 560 | 143 |
| 610 | 580 | 104 |
| 610 | 590 | 84 |
| 620 | 475 | 334 |
| 620 | 490 | 304 |
| 620 | 505 | 284 |
| 620 | 510 | 265 |
| 620 | 540 | 218 |
| 620 | 560 | 180 |
| 620 | 580 | 140 |
| 620 | 590 | 119 |
| 640 | 345 | 550 |
| 640 | 390 | 495 |
| 640 | 460 | 386 |
| 640 | 505 | 313 |
| 640 | 515 | 293 |
| 640 | 530 | 266 |
| 640 | 540 | 248 |
| 640 | 560 | 210 |
| 640 | 580 | 171 |
| 640 | 590 | 150 |
| 640 | 600 | 130 |
| 640 | 615 | 97 |
| 655 | 475 | 408 |
| 655 | 495 | 372 |
| 655 | 580 | 217 |
| 655 | 590 | 194 |
| 655 | 600 | 176 |
| 655 | 615 | 143 |
| 655 | 630 | 113 |
| 670 | 445 | 491 |
| 670 | 540 | 329 |
| 670 | 560 | 252 |
| 670 | 600 | 211 |
| 670 | 630 | 148 |
| 670 | 650 | 104 |
| 680 | 360 | 648 |
| 680 | 600 | 243 |
| 680 | 615 | 209 |
| 680 | 630 | 179 |
| 680 | 650 | 135 |
| 690 | 540 | 390 |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|-----------------|
| 690 | 580 | 313 |
| 690 | 600 | 272 |
| 690 | 615 | 239 |
| 690 | 630 | 209 |
| 690 | 650 | 165 |
| 690 | 670 | 119 |
| 700 | 450 | 541 |
| 700 | 580 | 350 |
| 700 | 600 | 309 |
| 700 | 615 | 276 |
| 700 | 630 | 246 |
| 700 | 650 | 202 |
| 700 | 670 | 157 |
| 720 | 515 | 511 |
| 720 | 580 | 388 |
| 720 | 615 | 314 |
| 720 | 670 | 195 |
| 720 | 680 | 160 |
| 720 | 700 | 124 |
| 740 | 600 | 387 |
| 740 | 630 | 323 |
| 740 | 680 | 199 |
| 740 | 700 | 163 |
| 740 | 715 | 115 |
| 740 | 720 | 95 |
| 750 | 490 | 640 |
| 750 | 580 | 458 |
| 750 | 615 | 393 |
| 750 | 670 | 274 |
| 750 | 700 | 203 |
| 750 | 715 | 154 |
| 750 | 730 | 117 |
| 770 | 580 | 521 |
| 770 | 615 | 447 |
| 770 | 650 | 373 |
| 770 | 700 | 257 |
| 770 | 715 | 208 |
| 770 | 730 | 171 |
| 770 | 745 | 137 |
| 790 | 650 | 443 |
| 790 | 670 | 397 |
| 790 | 700 | 327 |
| 790 | 715 | 278 |
| 790 | 735 | 241 |
| 790 | 760 | 177 |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|-----------------|
| 790 | 770 | 137 |
| 815 | 600 | 622 |
| 815 | 700 | 398 |
| 815 | 760 | 248 |
| 815 | 770 | 209 |
| 815 | 785 | 169 |
| 840 | 720 | 421 |
| 840 | 735 | 383 |
| 840 | 785 | 293 |
| 840 | 800 | 198 |
| 840 | 815 | 157 |
| 860 | 400 | 954 |
| 860 | 745 | 401 |
| 860 | 760 | 367 |
| 860 | 785 | 288 |
| 880 | 785 | 349 |
| 880 | 800 | 308 |
| 880 | 815 | 266 |
| 880 | 835 | 210 |
| 880 | 860 | 137 |
| 900 | 760 | 505 |
| 900 | 785 | 425 |
| 900 | 800 | 384 |
| 900 | 815 | 342 |
| 900 | 845 | 285 |
| 900 | 860 | 212 |
| 910 | 600 | 930 |
| 910 | 730 | 620 |
| 910 | 815 | 394 |
| 910 | 860 | 264 |
| 910 | 885 | 189 |
| 930 | 860 | 330 |
| 930 | 885 | 254 |
| 950 | 815 | 526 |
| 950 | 860 | 397 |
| 950 | 925 | 197 |
| 965 | 885 | 390 |
| 965 | 925 | 265 |
| 965 | 945 | 201 |
| 1000 | 650 | 1125 |
| 1000 | 860 | 566 |
| 1000 | 920 | 398 |
| 1000 | 945 | 303 |
| 1000 | 970 | 224 |
| 1050 | 926 | 571 |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.

EFALON® VIRGIN HOLLOW RODS

| Nominal O.D. mm | Nominal I.D. mm | Weight Gr/mm |
|-----------------------|-----------------------|-----------------|
| 1050 | 970 | 428 |
| 1050 | 1000 | 306 |
| 1050 | 1020 | 231 |
| 1120 | 925 | 900 |
| 1120 | 945 | 804 |
| 1120 | 1000 | 604 |
| 1120 | 1040 | 463 |
| 1120 | 1080 | 335 |
| 1200 | 1040 | 794 |
| 1200 | 1130 | 453 |
| 1200 | 1160 | 339 |
| 1215 | 1130 | 535 |
| 1215 | 1160 | 421 |
| 1260 | 1080 | 933 |
| 1260 | 1160 | 606 |
| 1260 | 1220 | 314 |
| 1300 | 1200 | 567 |
| 1300 | 1220 | 459 |
| 1300 | 1280 | 225 |
| 1320 | 1300 | 275 |
| 1340 | 1130 | 1113 |
| 1340 | 1280 | 473 |
| 1340 | 1300 | 384 |
| 1380 | 1220 | 949 |
| 1380 | 1300 | 626 |
| 1380 | 1340 | 453 |
| 1440 | 1300 | 933 |
| 1440 | 1380 | 564 |
| 1440 | 1400 | 444 |
| 1440 | 1420 | 332 |
| 1520 | 1420 | Ask |
| 1520 | 1470 | Ask |
| 1520 | 1520 | Ask |
| 1620 | 1470 | Ask |
| 1620 | 1520 | Ask |
| 1620 | 1570 | Ask |
| 1710 | 1570 | Ask |
| 1710 | 1610 | Ask |
| 1710 | 1660 | Ask |
| 1810 | 1660 | Ask |
| 1810 | 1770 | Ask |
| 1910 | 1460 | Ask |
| 1910 | 1500 | Ask |
| 2010 | 1850 | Ask |
| 2010 | 1950 | Ask |

| TOLERANCES | |
|------------|-----|
| O.D. | Ask |
| I.D. | Ask |
| Height | Ask |

On request, it can be produced in different dimensions. Max. Height is 100 mm.

You can calculate the piece's weight, multiplying Gr/mm by the height.